

# DL6790

## LED Voltage & Continuity Tester

The Di-log DL6790 CombiVolt 2 Digital Voltage & Continuity Tester with Phase Rotation test is the bench mark for voltage indicators. The three-in-one tester with a rugged, ergonomically formed housing for perfect handling is fully conformant to BS EN 64213-3:2014. The DL6790 also offers Single Phase Detection

### Features

- Meets safety and performance requirements of BS EN 61243-3 2014
- Continuity testing with optical and acoustic indication
- Automatic switching between voltage and continuity
- CAT IV 600V Safety Rated
- Phase rotation test system
- Single pole phase indication
- Fully compliant with GS38
- Fully operational voltage indication even when batteries are discharged



DL6780 Voltage Indicator Specification	
<b>2 Pole Voltage Indication</b>	
Voltage range	12 - 690V AC/DC
LED resolution	12, 24,50, 120, 230, 400 & 690V
Voltage detection	Automatic
Frequency range	0 - 400Hz
Peak current	3.5mA
Operation time	30 Seconds
Acoustic AC/DC signal	✓
Auto power on	<12V AC/DC
IP rating	IP65
<b>Single Pole Indication</b>	
Voltage range	100 - 690V AC
Frequency range	50 - 400Hz
<b>Continuity</b>	
Measurement range	0 - 400kΩ
<b>Phase Rotation Test</b>	
Voltage range	100 - 690V AC
Frequency	45 - 65Hz
Over voltage protection	690V AC/DC
<b>Other Information</b>	
Dimensions	225mm x 70mm x 28mm
Weight (net)	200g
Power supply	2 x 1.5V (RO3) AAA (supplied)
EAN	5060082542336



EMC & LVD  
EN 61326-1  
EN 61243-3:2014  
EN 61010-1  
EN 61010-2-030  
EN 61010-031  
EN 60529 (IP65)

**support@dilog.co.uk**

**Di-LOG Ltd**  
Unit 28 Wheel Forge Way  
Trafford Park  
Manchester M17 1EH  
UK  
Tel:+44 (0)161 877 0322  
Email: sales@dilog.co.uk  
Website: www.dilog.co.uk