

HVAC Meter PCE-HVAC 6



PCE-HVAC 6 HVAC meter

Up to 1000 A AC / DC / Non-contact voltage detection / Voltage measurement up to 600V. Temperature measurement via thermocouple / Robust rubberized housing

The HVAC meter PCE-HVAC 6 was specially developed for the tradesman in the field of heating, ventilation and air conditioning technology. This HVAC meter is ideal for many inspection and maintenance jobs in this area. This HVAC meter combines many gauges in one. It is possible with this meter to measure currents up to 1000 A in the DC and AC range via the clamp. Furthermore, voltages up to 600V AC / DC can be determined exactly. For quick and easy testing of electrical conductors, the HVAC meter is equipped with non-contact voltage detection.

The PCE-HVAC 6 HVAC meter can also measure resistors and capacitors. The diode test and continuity test complete the series of electrical measuring functions of the HVAC meter. As a special feature, the PCE-HVAC 6 HVAC meter has 2 measuring inputs for Type-K thermocouples. With the help of these thermocouples, for example, the flow and return temperature of heating systems can be measured.

The HVAC meter was developed for the everyday life of a service worker. The sturdy plastic housing withstands shocks easily. A circumferential rubber coating on the housing of the PCE-HVAC 6 helps ensure that the HVAC meter is secure in the hand, even when the technician wears gloves. The display is equipped with an LED backlight, which facilitates reading in dark environments. As a further highlight, the HVAC meter on the pliers tip has a measuring point illumination.

- ▶ Current measurement up to 1000 A
- ▶ Cover of the measuring sockets
- ▶ Voltage measurement up to 600V
- ▶ Temperature measurement via 2 thermocouples
- ▶ Display & measuring point illumination
- ▶ Non-contact voltage detection

Specifications

Current measurement DCA

Measuring range	Resolution	Accuracy (of measured value)
500 μ A	0.01 μ A	\pm (1% + 6 digits)
5000 μ A	0.1 μ A	\pm (1% + 6 digits)
50 A	0.01 A	\pm (2.5% + 5 digits)
1000 A	0.1 A	\pm (2.5% + 30 digits)

Current measurement ACA

Measuring range	Resolution	Accuracy (of measured value)
500 μ A	0.01 μ A	\pm (1.5% + 30 digits)
5000 μ A	0.1 μ A	\pm (1.5% + 30 digits)
50 A	0.01 A	\pm (2.5% + 30 digits)
1000 A	0.1 A	\pm (2.8% + 30 digits)

Note: For AC A measurements, this specification of accuracy refers to the range of 5% to 100% of the measuring range

Resistance measurement

Measuring range	Resolution	Accuracy (of measured value)
500 Ω	0.01	\pm (1% + 9 digits)
5 k Ω	0.0001	\pm (1% + 5 digits)
50 k Ω	0.001	\pm (1% + 5 digits)
500 k Ω	0.01	\pm (1% + 5 digits)
5 M Ω	0.0001	\pm (3% + 10 digits)
50 M Ω	0.001	\pm (3.5% + 10 digits)

Voltage measurement DCV

Measuring range	Resolution	Accuracy (of measured value)
500 mV	0.01 mV	\pm (0.1 % + 8 Digit)
5 V	0.0001 V	\pm (0.1 % + 4 Digit)
50 V	0.001 V	\pm (0.1 % + 4 Digit)
500 V	0.01 V	\pm (0.1 % + 4 Digit)
600 V	0.1 V	\pm (0.5 % + 4 Digit)

Voltage measurement AC V (50 Hz... 100 Hz)

Measuring range	Resolution	Accuracy (of measured value)
500 mV	0.01 mV	\pm (0.8 % + 9 Digit) (at 50 Hz / 60 Hz)
5 V	0.0001 V	\pm (1 % + 30 Digit)
50 V	0.001 V	\pm (1 % + 30 Digit)
500 V	0.01 V	\pm (1 % + 30 Digit)
600 V	0.1 V	\pm (1 % + 30 Digit)

Note: For AC V measurements, this specification of accuracy refers to the range of 5% to 100% of the measuring range

More information

Manual



More product info



Similar products



Subject to change

Capacitance measurement

Measuring range	Resolution	Accuracy (of measured value)
500nF	0.01	± (3.5% + 40 digits)
5000nF	0.1	± (3.5% + 10 digits)
50µF	0.001	± (3.5% + 10 digits)
500µF	0.01	± (3.5% + 10 digits)
5mF	0.0001	± (5% + 10 digits)

Frequency measurement

Measuring range	Resolution	Accuracy (of measured value)
50Hz	0.001	± (0.3% + 2 digits)
500Hz	0.01	± (0.3% + 2 digits)
5kHz	0.0001	± (0.3% + 2 digits)
50kHz	0.001	± (0.3% + 2 digits)
500kHz	0.01	± (0.3% + 2 digits)
5MHz	0.0001	± (0.3% + 2 digits)
10MHz	0.001	± (0.3% + 2 digits)

Duty cycle

Measuring range	Resolution	Accuracy (of measured value)
5% ... 95%	0.1	± (1% + 2 digits)

Pulsewidth: 100 µs ... 100 ms
Frequency: 10Hz ... 10 kHz

Temperature

Measuring range	Resolution	Accuracy (of measured value)
-100 ... 1000°C / -148 ... 1832°F	0.1	± (1% + 2.5°C / 3.5°F)

General technical data

Conductor diameter	Max. 4.8 mm / 1.9 in
Display	Two lines 50,000 digits
Continuity test	50 ohms / < 50 mA
Diode test	0.3mA / 2.8 V DC
Battery indicator	Battery icon when battery low
Overrange	OL, if measuring range exceeded
Sample rate	2Hz
Peak detection	> 1 ms
Thermocouple	Type K
Fuse	500mA ceramic quick-acting
AC bandwidth (AC A / AC V)	50Hz ... 400 Hz
AC measurement	True RMS
Operating conditions	5... 40°C / 41 ... 104°F, max. 80% RH at 31°C
Storage conditions	-20... 60°C / -4 ... 140°F, max. 80% RH
Power supply	9V block battery
Automatic shutdown	After about 30 minutes
Dimensions (W x H x D)	230 x 76 x 40 mm / 9 x 3 x 1.6 in
Weight	315g / < 1 lb
Safety	IEC 1010-1 (2001); EN 61010-1 (2001) CAT III 600V CAT II 1000V Degree of pollution 2

Subject to change

